



Smart, Optimal, Dependable Charging



480/600VAC HF Conventional Modular Charger

Industrial Battery Charger (Designed for Deka lead battery technology)

SPECIFICATION REFERENCE							
NUMBER OF BATTERY CELLS	MODEL NUMBER	BATTERY AMP-HOUR CAPACITY FOR 8 HRS.	DC OUPTPUT AMPS	PHASE	AC INPUT AMPS AT 480 VAC 60HZ-3 PH	AC INPUT AMPS AT 600 VAC 60HZ-3 PH	APPROX. WEIGHT (LBS.)
12	400EB1-12	400	65	3	2.7	2.1	54
12	600EB2-12	550	98	3	4.0	3.2	66
12	750EB2-12	750	122	3	5.0	4.0	66
12	900EB2-12	900	147	3	6.0	4.8	66
12	1000EB3-12	1000	163	3	6.7	5.3	79
12	1200EB3-12	1200	196	3	8.0	6.4	79
12,18	400EB1-18	400	65	3	4.0	3.2	54
12,18	550EB2-18	550	90	3	5.5	4.4	66
12,18	750EB2-18	750	122	3	7.5	6.0	66
12,18	900EB2-18	900	147	3	9.0	7.2	66
12,18	1000EB3-18	1000	163	3	10.0	8.0	79
12,18	1200EB3-18	1200	196	3	12.0	9.6	79
12,18	1375EB3-18	1375	224	3	13.7	11.0	79
12,18	1800EB4-18	1800	293	3	17.9	14.3	92
12,18,24	350EB1-24	350	57	3	4.7	3.7	54
12,18,24	600EB2-24	600	98	3	8.0	6.4	66
12,18,24	765EB3-24	765	125	3	10.2	8.2	79
12,18,24	900EB3-24	900	147	3	12.0	9.6	79
12,18,24	1000EB3-24	1000	163	3	13.3	10.6	79
12,18,24	1200EB4-24	1200	196	3	16.0	12.8	92
12,18,24	1400EB4-24	1350	220	3	18.0	14.4	92
12,18,24	2000EB6-24	2000	326	3	26.6	21.3	150
12,18,24,36,40**	450EB2-40	450	73	3	9.9	7.9	66
12,18,24,36,40**	700EB3-40	700	114	3	15.5	12.4	79
12,18,24,36,40**	925EB4-40	925	151	3	20.5	16.4	92
12,18,24,36,40**	1150EB5-40	1150	187	3	25.4	20.3	139
DIMENSIONS							
MODEL NUMBERS EB1-EB4: 14"H x 14"W x 16"D				MODEL NUMBERS EB5-EB8: 28"H x 14"W x 16"D			

** Control does not auto select between 36 and 40 cell



Sales Hotline: 610-682-3260

e-mail: motivepowersales@dekabatteries.com



East Penn Manufacturing Co.

Lyon Station, PA 19536-0147

Phone: 610-682-6361

Fax: 610-682-4781

www.dekabatteries.com

E.P.M. Form No. 2666 11/22

© 2022 by EPM Printed in U.S.A.

Data subject to change without notice. No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.